

**OUR BEST IN OVERVIEW**

FIND THE SLICING AND PORTIONING MACHINE THAT SUITS YOU!



**IC 700/1100**

**ICC 25**

**ICC 28**

	IC 700/24 (B)	IC 1100/24 (B)	IC 700/36 (B)
Max. input length mm	700	1100	700
Cross section mm (WxH)	250 x 240	250 x 240	360 x 220
Dimensions mm (LxWxH) (L incl. belt)	1925 x 950 x 1420 (2990)	2725 x 950 x 1420 (3390)	1925 x 1175 x 1420 (2990)
Connection (other voltage on request)	400 V / 5,8 kW	400 V / 5,8 kW	400 V / 5,8 kW
Weight kg	320	360	450
Performance single blade slices/minute	up to 300 (optional 400)	up to 300 (optional 400)	up to 300 (optional 400)
Performance double blade slices/minute (continuous)	up to 600 (optional 800)	up to 600 (optional 800)	up to 600 (optional 800)
Cutting length in mm	0,5 - 700	0,5 - 1000	0,5 - 700

	ICC 25	ICC 28	ICC 28 with scanning unit
Max. input length mm	variable	variable	variable
Cross section mm (WxH)	250 x 180	280 x 180	280 x 180
Dimensions mm (LxWxH)	3574 x 1047 x 1611	3710 x 1077 x 1715	5206 x 1077 x 1715
Connection (other voltage on request)	400 V / 10 kW	400 V / 10 kW	400 V / 10 kW
Weight kg	850	850	1020
Performance single blade slices/minute	60 - 500	60 - 600	60 - 600 (up to 200 slices incl. scanning device)
Performance double blade slices/minute (continuous)	-	-	-
Cutting length in mm	0,5 - infinite	0,5 - infinite	0,5 - infinite

**FUNCTIONS**

	IC 700/24 (B)	IC 1100/24 (B)	IC 700/36 (B)	ICC 25	ICC 28	ICC 28 with scanning unit
Start devine	✓	✓	✓	✓	✓	✓
Flap start	✓	✓	✓	-	-	-
Return limiter	✓	✓	✓	-	-	-
Distribution of remaining slice	✓	✓	✓	✓	✓	✓
Slicing software	✓	✓	✓	✓	✓	✓
Weight optimized slicing	✓	✓	✓	-	-	-
Fixed weight slicing	-	-	-	-	-	✓