

OUR BEST IN OVERVIEW

FIND THE MULTI-PURPOSE DICER THAT SUITS YOU!



	MHS 850/1000		MHS 1700/2000		MHS 2400/3100		MHS 2900	MHS 3200/4000	
	MHS 850 -90 / -96	MHS 1000 -90 / -96	MHS 1700 -105 / -112	MHS 2000 -105 / -112	MHS 2400 -120 / -126	MHS 3100 -140	MHS 2900 -120	MHS 3200	MHS 4000
Max. input length mm	310	530	370	530	530	530	620	620	620
Cross section mm (WxH)	90 x 90 / 96 x 96	90 x 90 / 96 x 96	105 x 105 / 112 x 112	105 x 105 / 112 x 112	120 x 120 / 126 x 126	140 x 140	120 x 120	120 x 120	250 x 150
Throughput kg/h (with highest feed & opt. chamber filling)	850 / 950	1000 / 1100	1600 / 1800	1900 / 2100	2400 / 2600	3100	2900	3200	4000
Cutting length in mm	0 - 35	0 - 35	0 - 45	0 - 45	0 - 45	0 - 45	0 - 50	0 - 50	0 - 60
Grid sizes in mm	4, 5, 6, 7, 8, 10, 13, 15, 18, 22, 30, 45		5, 6, 7, 8, 10, 13, 15, 18, 21, 26, 35, 52		4, 5, 6, 8, 10, 12, 15, 20, 24, 30, 40, 60	5, 6, 7, 8, 10, 14, 18, 20, 24, 28, 35, 46, 70	4, 5, 6, 8, 10, 12, 15, 20, 24, 30, 40, 60	4, 5, 6, 8, 10, 12, 15, 20, 24, 30, 40, 60	5, 6, 7, 8, 10, 13, 15, 19, 21, 25, 30, 38, 50, 75
Dimesions mm (LxWxH)	1100 x 650 x 1065	1520 x 650 x 1065	1645 x 1520 x 1050	1920 x 1520 x 1050	2030 x 1010 x 1490	2030 x 1010 x 1490	2265 x 950 x 1200	3500 x 1505 x 2065-2750	3550 x 1785 x 2330-3015
Connection (other voltage on request)	400 V / 2,6 kW	400 V / 2,6 kW	400 V / 4,8 kW	400 V / 4,8 kW	400 V / 5,6 kW	400 V / 5,6 kW	400 V / 6,5 kW	400 V / 11,3 kW	400 V / 15,3 kW
Weight kg	235	275	515	540	430	450	700	1700	2100
FUNCTIONS									
Adjustable longitudinal precompression	✓	✓	✓	✓	✓	✓	✓	✓	✓
4-side precompression	- / ✓	- / ✓	- / ✓	- / ✓	- / ✓	-	-	-	-
Lateral compression	-	-	-	-	-	-	-	✓	✓
Speed control grid drive and slice-cut blade	-	-	-	-	-	-	-	✓	✓
Conveyor belt	✓	✓	✓	✓	✓	✓	✓	✓	✓
Automatic loading	-	-	-	-	-	-	✓	✓	✓